

TRAFFIC-LINE Steel Hoop Guard with Gate



Designed specifically for use with TRAFFIC-LINE Steel Hoop Guards and Steel Hoop Guards XL, these gates are manufactured in high quality steel complete with welded in panel for extra strength which can be used for attaching warning signs (signs not supplied).

The gate is attached to either the 48 mm or 60 mm Ø Hoop Guard by a pre-assembled adapter bracket. The gate can be operated either manually or self-closing by means of a gas cylinder. The unique fitting technology enables the gate to hinge to either the left or to the right and allow the gate to open (90°) inwards or outwards. Supplied with a 1 metre wide Hoop Guard.

Finish:
Powder coated yellow.

- Indoor use only
- For 48 and 60 mm Ø Hoop Guards
- Manual and Self-closing options

Option:
Can be retrofitted to existing installations.

For gate dimensions see page 23.



	Gate	Dimensions (mm) Ø x Height x Width	Delivery weight (kg/ea.)	Reference
Gate-powder coated with pre-assembled adapter for fitting to hoop guard	Manual	48 x 1,000 x 1,920	22.5	201.22.589
		60 x 1,000 x 1,920	28	201.25.603
	Self-closing with gas cylinder	48 x 1,000 x 1,920	22.5	201.21.134
		60 x 1,000 x 1,920	28	201.28.583
Through bolt 12/120 (4 per Unit)				109.24.665
Surface fixing bolt with Sleeve 8/100 (4 per Unit)				109.17.393

TRAFFIC-LINE Steel Hoop Guards – Light Duty



These additions to our popular range of Hoop Guards are manufactured in 40mmØ steel with a 1.5mm wall thickness. Ideal for areas which require less heavy protection as provided by our standard range of Hoop Guards. Intended for indoor use only they are finished in an eye-catching powder coated yellow with black bands. Quickly and easily installed using 8 fixing bolts per guard.


Ideal for use in segregating work zones in factories and warehouses etc.

Finish:
Indoor use only:
Powder coated yellow with black bands.

Diameter:
40mm Ø x 1.5mm wall thickness.

- Indoor use only
- Available in various widths
- With reinforcing bar
- Cost effective

Mounting method:
For surface fixing:
Base plate 150 x 150 x 6 mm.



Description	Height/length (mm)	Delivery weight (kg/ea.)	Reference
Floor mounting With mounting plates 150 x 150 x 6 mm	1,000 x 1,000	9	201.24.623
	1,000 x 1,500	11	201.28.976
	1,000 x 2,000	13	201.25.587
Through bolt anchor (4 per bollard)			109.24.665
Surface fixing bolt S12 8/100 (4 per guard)			109.17.393