











TECHNICAL SPECIFICATIONS

Length of one unit: 3000 mm.
 Total depth: 1500 mm.
 Extension with intermediate module: 1000 mm.
 Square posts: steel tubes 100 x 60 mm.
 Under roof height: 2200 mm.
 Roof: tinted UV-resistant 6 mm PMMA glazing.
 Roof frame: 40 x 40 mm steel tubes with rain gutter.
 Beams: 5 mm gauge steel sheet.
 Rear and side cladding: 8 mm Securit[®] safety glass or perforated steel.
 Cladding attachments: pinch-grip system made from Zamak alloy with brushed finish.
 Bus stop sign: 160 mm high x 900 mm wide, galvanised steel lacquered in RAL 9006.
 Timetable display case: 750 x 750 x 30 mm in anodised aluminium.
 Advertising space: light box (1710 mm x 1160 mm display area) or "2000" display case (1710 mm x 1200 mm display area).
 Finish: galvanised and painted in our colours.
 Installation: concreted directly into ground.



PAINT FINISH

				
Procity Grey	RAL 9010	RAL 5010	RAL 3020	RAL 9005
				
RAL 7044	RAL 3004	RAL 6005	RAL 8017	Corten effect

TECHNICAL SPECIFICATIONS

The standard Conviviale version leaves the pavement clear with the minimum footprint ensuring that pedestrians can easily circulate.

The standard version is available in length 3000mm and equipped with a timetable case 750 x 750mm (6 A4). The shelter can be extended using 1000mm modules to achieve the required length adapted to the number of passengers.

The shelter also exists in a mini version 1000mm for less frequented locations.

Configuration combinations:

- Advertising space – A double-sided light box or poster case (display size H1710 x 1160mm or H1750 x 1200mm)
- One or two side cladding panels

Options: Bench, perch seat, signage flag, LED lighting kit powered by a photovoltaic panel or a mains power source, wind and snow guards.











- Length of one unit: 3000 mm
- Total depth: 1500 mm
- 100 x 60 mm steel verticals
- Roof structure in 40 x 40 mm steel tubes
- 5 mm sheet steel roof supports
- Roof glazing in smoked UV inhibited 6 mm PMMA

Cladding attachments: pinch-grip system made from Zamak alloy with brushed finish
Zinc primed and finished in our standard RAL colours.

Installation: Concreted directly into the ground.



PAINT FINISH

				
Procity Grey	RAL 9010	RAL 5010	RAL 3020	RAL 9005
				
RAL 7044	RAL 3004	RAL 6005	RAL 8017	Corten effect