



### Truck entry aid, angled

made of Ø 152.4 mm round tube,  
total length: approx. 3000 mm,  
for plugging down

|  | Kg   | Part-No. |
|--|------|----------|
| <b>hot-dip galvanized</b>  |      |          |
| left side  | 49.0 | 40157L   |
| right side   | 49.0 | 40157R   |
| <b>hot-dip galvanized and white coated<br/>with red reflecting stripes</b> |      |          |
| left side  | 49.0 | 40157LB  |
| right side   | 49.0 | 40157RB  |
| <b>hot-dip galvanized and yellow coated<br/>with black stripes</b>         |      |          |
| left side  | 49.0 | 40157LBG |
| right side   | 49.0 | 40157RBG |

### Truck entry aid, straight

can also be used as extension element  
made of Ø 152.4 mm round tube,  
total length: approx. 3600 mm,  
for plugging down

|  | Kg   | Part-No. |
|--|------|----------|
| <b>hot-dip galvanized</b>  | 54.0 | 40157G   |
| <b>hot-dip galvanized and white coated<br/>with red reflecting stripes</b> | 54.0 | 40157GB  |
| <b>hot-dip galvanized and yellow coated<br/>with black stripes</b>         | 54.0 | 40157GBG |



**pittman**<sup>®</sup>