

# 453 Skywalker<sup>®</sup> II PUR ESD

ESD polyurethane mat with pebble pattern



# Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

## 453 Skywalker® II PUR ESD

High quality polyurethane foam anti-fatigue mats are reputed for their ultimate comfort in stationary standing positions.

- All four sides have bevelled edges to minimize tripping hazards
- Pebble surface provides sure footing and allows freedom of movement
- Environmental friendly, produced without use of organic carbon-based blowing agents

### Recommended use


- Dry Areas
- Ideal for stationary standing workstations, sit-stand desks, packing stations, office environments, reception areas, wait stations, service counters, cashiers
- Medium duty

### Colors:

- Black

### Sizes:

- 65cm x 135cm
- 65cm x 175cm
- 65cm x 90cm
- 90cm x 125cm
- 90cm x 155cm
- 90cm x 185cm



# Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

## Skywalker® II PUR ESD

### General

Brand	Notrax
Category	ESD Matting & Accessories
Product Number	453
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Skywalker® II PUR ESD
Recommended use	Ideal for stationary standing workstations, sit-stand desks, packing stations, office environments, reception areas, wait stations, service counters, cashiers
Type	Dry Areas - Medium Duty Polyurethane Mats
Update trigger	20210310-1301
Usage Intensity	Medium duty

### Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	False
Sustainability	Recyclable material
Warranty	1

### Tests

Abrasion Resistance 1000	150 mg (2.5N)
Elongation	300%
ESD Rg	Rp 10 <sup>6</sup> - 10 <sup>9</sup>
ESD Rp	Rg 10 <sup>6</sup> - 10 <sup>9</sup>
Hardness	25 Shore A
Slip Rating	R11
Surface Flammability	Pass
Tear Strength	1.7 N/mm

### Technical Specifications

Application	Industrial Environments
Edges	Bevelled edges on all sides
Material	Nitrile rubber blend
Material Group	Polyurethane
Process	Injection Moulding
Temperature Range	- 40 ° C up to + 120 ° C