pittman®

015 Uni Standard™

Printed uni-colour entrance mat



Logo Matting - Printed Mats 015 Uni Standard™

Uni Standard[™] is a mono-coloured mat printed in any colour to match your mat to any interior scheme or to use together with the custom printed logo mats for a colour coordinated matting system.

- A durable vinyl backing with smooth finish adapts to any surface
- Tufted velours cut loop pile consisting of 100% noncrush polyamide 6.0 high twist yarns.
- 405 grams of yarns per m²

Recommended use

- Indoor
- For placement inside entrances of offices, shops,
- restaurants, grocery shops, bakeries, specialty stores.Light traffic

Colors:

Off White

Sizes:

- 120cm x 180cm
- 60cm x 90cm
- 90cm x 120 cm
- 90cm x 150cm
- 90cm x 300cm
- 120cm x linm
- 90cm x linm

Accessories:

083 Bevelled Nosing 2 mm

WATER RETENTION

CRUSH RESISTANCE

RATING DUST CONTROL

B2 Athy Business Campus Athy Co. Kildare R14 PK74 sales@pittman.ie 01 5312777 1310 Solihull Parkway Birmingham Business Park Birmingham B37 7YB sales@pittman.uk 0121 630 3527

Logo Matting - Printed Mats Uni Standard™

General

| Brand | Notrax |
|-------------------|---|
| Category | Printed Mats |
| Product Number | 015 |
| Product Family | Industrial & Commercial Matting |
| Product Group | Logo Matting |
| Product Name | Uni Standard™ |
| Recommended use | For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, specialty stores. |
| Shipping Location | Barendrecht 2992SB, The Netherlands |
| Туре | Indoor Absorbant - Printed Mats |
| Update trigger | 20210310-1301 |
| Usage Intensity | Light traffic |

Sustainability

| REACH | Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals). |
|----------------|--|
| Sustainability | Recyclable material, Contributes to a cleaner environment by reducing need of cleaning chemicals |
| Warranty | 1 |

Tests

| Comfort Class | LC2 |
|------------------|------|
| Light Fastness | 5 |
| Organic Solvents | 4 |
| Rubbing Fastness | 4 |
| Salt Water | 4 |
| Shampoo | 4 |
| Static Charge | <0.1 |
| Water Fastness | 4 |

B2 Athy Business Campus Athy Co. Kildare R14 PK74 sales@pittman.ie 01 5312777 1310 Solihull Parkway Birmingham Business Park Birmingham B37 7YB sales@pittman.uk 0121 630 3527

Technical Specifications

| Absorption Capacity | 3 l/m² |
|-----------------------|------------------------------------|
| Backing | Black vinyl (DOP free) |
| Dimensional Stability | <0.4 |
| Edges | Vinyl borders: 2.5 cm on all sides |
| Material | 100% polyamide 6.6 yarns |
| Material Group | Polyamide |
| Pile Weight (g) | 405 |
| Primary Backing | Nonwoven PET/PA |
| Process | Tufting |
| Tufts | 962m ² |
| Yarn Construction | Cut loop pile - velours |

B2 Athy Business Campus Athy Co. Kildare R14 PK74 sales@pittman.ie 01 5312777

1310 Solihull Parkway Birmingham Business Park Birmingham B37 7YB sales@pittman.uk 0121 630 3527