

# 150 Aqua Trap®



- Ultra resistant carpet mat constructed to withstand the heaviest of foot traffic.
- Unsurpassed ability to scrape debris from shoes while maintaining its great looking appearance for the longest time.
- Textile top surface high pressure molded into a bubble design indestructible rubber base.
- Patented perimeter “Aqua Dam” and rounded corners form a tray that can hold up to 6 liters of water per square meter.
- Anti-Microbial carpet treatment to stop bacteria and germs at the entrance.
- Unique slip resistant gripper pattern on the back.
- Suitable for even the heaviest of traffic conditions.
- For placement inside entrances in schools, universities, public buildings, sports facilities, shopping malls.
- Vacuum or use extraction method to clean or hose off with water and hang to dry.

# 150 Aqua Trap®

PRODUCT SPECIFICATIONS		
Designation	Dust Control Matting	
Description	Absorbent /scrape carpet mat	
Material		
	Top	Tufted loop pile carpet consisting of absorbing Decalon® yarns is permanently bonded on to a heavy duty contour moulded rubber base 850 grams of yarns per m <sup>2</sup>
	Backing	Synthetic rubber with gripper pattern
Process	Tufted loop pile, bonded on a contour-moulded synthetic rubber base	
Category	Indoor absorbent - Heavy duty	
Recommended use	Indoor - heavy foot traffic	
Colours	Blue, Green, Charcoal, Brown, Red, Burgundy, Grey	
Weight	5.2 kg/m <sup>2</sup>	
Thickness	13 mm	
Standard sizes	60 cm x 90 cm 90 cm x 150 cm 120 cm x 180 cm 120 cm x 300 cm	
Custom sizes	N/A	
Special remarks	Patented raised perimeter « Aqua Dam »	

PRODUCT TESTING		
Tests	Norms	Results
Abrasion resistance	ASTM D3884	0.9% weight loss
Colour fastness to light	AATCC 16E	
Accelerated wear test by sim floor machine	U.S.	4
Accelerated soiling	U.S.	4
Anti-slip	DIN51130 BGR181	
Water retention	ISO 4920 TNO W6034	3.6 l/m <sup>2</sup>
Sanitary epidemiologic test	GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044984.07.09

ANTIBACTERIAL ACTIVITY TESTING		
Resistance to Escherichia coli	ASTM E2149-01	Pass
Resistance Penicillium chrysogenum	AATCC 30	No growth

FIRE TESTING			
	Surface Flammability	ASTM D2859	Pass
	Classification of the reaction to fire performance	DIN EN 13501-1	

Sustainability	<ul style="list-style-type: none"> <li>• Recyclable material</li> <li>• REACH compliant ( Registration, Evaluation, Authorization and restrictions of Chemicals)</li> <li>• Contributes to cleaner environment by reducing need of cleaning chemicals</li> </ul>	
----------------	--	--