

# 417 Bubble Sof-Tred™

Dyna-Shield™ layer with unique bubble design



# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths 417 Bubble Sof-Tred™

Exceptional worker comfort due to 12.7 mm thick specially formulated compound. Protective layer of exclusive Dyna-Shield™ extends service life by 50% compared to regular microcellular vinyl.

- Available with yellow borders along sides to comply with OSHA code 1910-144
- All 4 sides are bevelled and sealed to minimize tripping hazards
- Unique bubble design provides exceptional comfort

#### Recommended use


- Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Medium duty

#### Colors:

- Black/Yellow
- Grey

#### Sizes:

- 60cm x 91cm
- 91cm x 150cm
- 122cm x 18.3m
- 60cm x 18.3m
- 91cm x 18.3m



**pittman**®

# Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths Bubble Sof-Tred™

## General

Brand	Notrax
Category	Dry Areas Linear Lengths
Product Number	417
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Bubble Sof-Tred™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States
Type	Dry Areas - Dyna Shield™
Update trigger	20210310-1301
Usage Intensity	Medium duty

## Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material
Warranty (years)	1

## Tests

Abrasion Resistance 1000	1.7%
Abrasion Resistance 500	0.6%
Compression Deflection 1.4	0.70 cm
Compression Deflection 2.8	0.81 cm
Elongation	140.8%
Fire rating US	Pass
Foam Battery	40 lb/in <sup>2</sup>
Hardness	20 Shore A
Slip Rating	R10
Coefficient Friction Dry	1.10
Surface Flammability	Pass
Tear Strength	13 lb



## Technical Specifications

Application	Industrial Environments
Breaking Load	24.4 lb
Edges	Bevelled edges on all sides
Material	Microcellular vinyl
Material Group	Vinyl
Process	Foaming

