

Defender Anti-Nudge Warehouse Bollard Ø 193mm

OVERVIEW

The Defender Anti-Nudge Warehouse Bollard provides heavy-duty protection for warehouses, loading bays and industrial environments, helping to protect buildings, equipment and restricted areas from forklift and vehicle impacts.

Manufactured from hot-dip galvanised steel, this bollard offers excellent resistance to rust and corrosion, making it suitable for both indoor and outdoor use.

Its Ø193mm steel construction with a 3.6mm wall thickness provides robust, long-lasting protection in busy areas with frequent forklift, pallet truck and HGV movement. Available in 1500mm and 2000mm heights, with plain galvanised or powder-coated yellow finishes.

The removable, non-locking design allows the bollard to be easily lifted out when vehicle access is required. Supplied with a ground socket for installation 500mm below the surface, it provides a practical solution for areas where access requirements may change. A locking option is also available separately.

FEATURES

- **Heavy-Duty Protection –** Ø193mm steel construction with 3.6mm wall thickness for reliable impact protection.
- **Corrosion Resistant –** hot-dip galvanised steel provides long-lasting protection against rust.
- **Removable Design –** non-locking bollard allows quick and easy removal when vehicle access is required.
- **Ground Socket Installation –** supplied with a socket for concrete-in installation 500mm below ground level.

TECHNICAL DATA

SPECIFICATION	DETAILS			
Design	Powder Coated Yellow		Galvanised	
Product code	763491	763493	763490	763492
Height	1500 mm	2000 mm	1500 mm	2000 mm
Diameter	193 mm			
Wall Thickness	3.6 mm			
Material	Galvanised Steel			
Finish	Hot-dip galvanised steel - protected agains rust			
Mounting	Ground socket inserts directly into the ground 500mm below surface			

DRAWINGS

