

# Defender Warehouse Bollard Ø 273mm

## OVERVIEW

The Defender Warehouse Bollard Ø273mm provides heavy-duty impact protection for warehouses, distribution centres, loading bays and industrial environments, helping to protect buildings, machinery and valuable infrastructure from accidental vehicle damage.

Manufactured from hot-dip galvanised steel with a 5mm wall thickness, this bollard offers excellent resistance to rust and corrosion, making it suitable for both indoor and outdoor use.

Its substantial Ø273mm steel construction provides robust protection in areas with frequent forklift and heavy vehicle movement. Available in 1500mm and 2000mm heights for sub-surface installation, or 1500mm for surface mounting, the bollard comes in plain galvanised or powder-coated yellow with black bands.

The bollard is available with two installation options to suit different requirements. The sub-surface version is cast directly into concrete, while the surface-mounted version features a bolt-down base plate for installation onto existing concrete surfaces. An optional steel cap is also available for sub-surface models, allowing concrete filling for additional strength.

## FEATURES

- **Heavy-Duty Protection –** Ø273mm steel construction with a 5mm wall thickness for demanding industrial environments.
- **Corrosion Resistant –** hot-dip galvanised steel provides long-lasting protection against rust.
- **Flexible Installation –** available in surface-mounted or sub-surface options to suit different applications.
- **Optional Concrete Filling –** steel cap option for sub-surface models allows additional reinforcement.

## TECHNICAL DATA

| SPECIFICATION | DETAILS | | | | | |
|---|---|---|---|---|---|---|
| Design | Powder Coated Yellow | | | Galvanised | | |
| Product code | 752545 | 752544 | 752543 | 752566 | 756567 | 752568 |
| Total Height | 1500 mm | 2000 mm | 1500 mm | 1500 mm | 2000 mm | 1500 mm |
| Mounting | Sub-Surface | Sub-Surface | Surface Mount | Sub-Surface | Sub-Surface | Surface Mount |
| Diameter | 273 mm | | | | | |
| Material | Plain galvanised or galvanised with yellow/black warning stripes | | | | | |
| Wall Thickness | 5 mm | | | | | |
| Finish | Hot-dip galvanised steel - protected agains rust | | | | | |

## DRAWINGS

