

620 Diamond Flex Lok™

Diamond Flex Lok™ modular PVC platform



Ergonomic, Anti-fatigue & Safety Matting - Wet Areas Modular Matting 620 Diamond Flex Lok™

Sensational fatigue relief due to its unique “flex” design underneath. Drainage system of round shaped holes of 22 mm diameter facilitates the removal of liquids and debris from the work area without clogging, keeping the surface clear.

- Available pre-assembled or as loose tiles for on-site installations
- A permanent interlocking system ensures that the mat will not come apart, no gluing required
- Anti-slip deck-plate surface design, tested R10 according to DIN51130 and BG-rule BGR181
- Bevelled ramps are available, eliminating trip hazards and allowing for easy access on to and off of the mat surface

Recommended use

- Wet/Dry and Oily Areas
- In manufacturing plants, production lines, assembly lines, CNC machines, metal working, fabrication
- Heavy duty

Colors:

- Black
- Black/Yellow

Sizes:

- 107cm x 152cm
- 107cm x 183cm
- 76cm x 152cm
- per m2

Accessories:

- 620-Tile Diamond Flex-Lok™ Tile
- 620-Ramp Diamond Flex-Lok™ Bevel
- 620-Corner Diamond Flex-Lok™ Corner



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE



Ergonomic, Anti-fatigue & Safety Matting - Wet Areas Modular Matting Diamond Flex Lok™

General

| | |
|-------------------|---|
| Brand | Notrax |
| Category | Wet Areas Modular Matting |
| Product Number | 620 |
| Product Family | Industrial & Commercial Matting |
| Product Group | Ergonomic, Anti-fatigue & Safety Matting |
| Product Name | Diamond Flex Lok™ |
| Recommended use | In manufacturing plants, production lines, assembly lines, CNC machines, metal working, fabrication |
| Shipping Location | Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States |
| Type | Wet/Dry and Oily Areas - Heavy Duty Modular Systems |
| Update trigger | 20210310-1301 |
| Usage Intensity | Heavy duty |

Sustainability

| | |
|----------------|---|
| REACH | Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals). |
| Rohs US | Rohs compliant (Restriction of Hazardous Substances). |
| Sustainability | Recyclable material |
| Warranty | 1 |

Tests

| | |
|--------------------------|-----------------------|
| Fire rating EU | En 13501-1 Cfl-S2 |
| Foam Battery | 40 lb/in ² |
| Hardness | 85 Shore A |
| Slip Rating | R10 |
| Coefficient Friction Dry | 0.69 |

Technical Specifications

| | |
|---------------------|---|
| Application | Industrial Environments |
| Chemical Resistance | Cat. V PVC |
| Edges | Attachable bevelled edges are available |
| Material | PVC |
| Material Group | PVC |
| Process | Injection Moulding |