DURABEL LITE Stainless Steel Mirrors



The **DURABEL LITE** is an inexpensive alternative to pure stainless steel convex mirrors. A highly polished distortion free stainless steel mirror face is mounted in a weather resistant ABS plastic frame which combines the cost advantages of plastic with the durability of stainless steel. This mirror is particularly suitable for installation in areas of high air pollution and vandalism. The **DURABEL LITE** offers a long life without loss of image quality making the mirror a very economic purchase.

The universal clamp supplied can be used with posts of 60–90mm Ø with no requirement for adapters.

The **DURABEL LITE** is highly suitable for use in areas of traffic regulation, blind spots, production processes, warehouses, manufacturing sites, marshalling yards, logistics depots etc.

- Indoor and Outdoor use
- Exceptional image quality
- · Mirror surface of Stainless Steel
- Virtually indestructible
- · Inexpensive
- Eye catching red/white surround
- 5 year guarantee against manufacturing faults









The **DURABEL LITE IceFree** Stainless Steel mirror is a low cost alternative to our DURABEL IceFree mirror, but retains the tried and tested thermo-gel system which controls the surface temperature of the mirror based on the actual ambient temperature. This system prevents the formation of condense and ice on the mirror surface down to -20°C.

The mirror surface and universal mounting are manufactured in stainless steel with the housing manufactured in weather resistant white ABS complete with reflective red stripes.

This mirror is particularly suited for use in locations which experience extreme weather conditions and/or which do not have a suitable electric supply.

The universal clamp supplied can be used with posts of 60-90mm Ø with no requirement for adapters.

- High quality stainless steel mirror surface
- Effective control down to -20° C
- No costly electric supply required
- Effectively reduces condensation and ice formation
- 5 year guarantee against manufacturing faults





	DURABEL LITE	Mirror size (mm)	Max. obs. dist. from mirror (m)	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
	LITE 1	450 x 600	6	7.9	242.20.223	
NE	LITE 2	600 x 800	10	11.1	242.26.946	5 / 10 days
	N! LITE 3	800 x 1,000	15	12.9	242.20.654	
	LITE 600	600 Ø	4	9.2	242.22.647	

DURABEL IceFree ECO	Mirror size (mm)	Max. obs. dist. from mirror (m)	Delivery weight (kg/ea.)	Reference	Typical despatch time (working days)
1	450 x 600	6	15	242.24.151	
2	600 x 800	10	23.5	242.27.488	
3	800 x 1,000	15	34	242.25.771	5 / 10 days
600	600 Ø	6	15	242.20.096	
800	800 Ø	10	23.5	242.28.986	