


Slip-resistant workplace matting that's light to handle and super versatile.



**Certified slip resistant with excellent drainage and anti-fatigue benefits, Heronair is perfect for light industrial workplaces and walkways where there's a risk of water underfoot.**

Made from non-porous PVC with an etched pattern, Heronair is impermeable to fluids and provides excellent drainage, making it ideal for environments where spillages are likely. The hollow construction makes it light to lift and easy to move, so installation is quick and cleaning is simple.




Features:

Etched surface	Two layer, tubular construction	Made from non-porous PVC	Fatigue reducing and insulating	Comes in 10m (33') rolls



Benefits:

Certified slip resistant (DIN 51130:R11, ASTM 1677:0.6/0.6)	Excellent drainage (DIN 51130:V10)	Chemical, oil and acid resistant	Boosts productivity	Simple to install, easy to clean



### Standard sizes:

<b>Product</b>	<b>Heronair</b>
<b>Height</b>	10mm (3/8")
<b>Standard roll options</b>	10 x 0.5m (33' x 1'8")
	10 x 0.75m (33' x 2'5")
	10 x 1m (33' x 3'3")
<b>Weight</b>	4.5kg/m <sup>2</sup> (0.6lbs/sq.ft)

### Tolerances:

	<b>Height (+/- 0.5mm)</b>	<b>Length (0+0.3m)</b>	<b>Width (+/- 1cm)</b>
<b>Heronair</b>	10mm	10m	50cm 75cm 100cm

All dimensions are nominal

### Technical information:

<b>Acoustic</b>	Excellent sound absorption
<b>Chemical</b>	Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this <a href="#">information sheet</a> .
<b>Composition</b>	Flexible Polyvinyl Chloride (PVC)
<b>Environment</b>	Heronair is 100% recyclable. When manufactured in black, it's made using our post industrial recycled material. The recycled content averages at least 30%, but we strive for 100% wherever possible. We don't use any substances included in the SVHC list under REACH in any of our matting products..
<b>Fire</b>	DIN 4102 Part I – Classification B2
<b>Hygiene</b>	Made from non-porous PVC that's naturally resistant to bacteria growth.
<b>Reversion</b>	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by <a href="#">downloading this information sheet</a> .
<b>Slip resistance</b>	ASTM F 1677- Dry/Wet: 0.6/0.6 DIN 51130: RI I, VI0
<b>Thermal</b>	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
<b>UV light</b>	Resistant to PVC degradation
<b>Warranty</b>	Two years. Visit our <a href="#">policies page</a> for more information about warranties

### Installation:

Heronair's one-piece construction means installation is simple:


- Comes in 10m rolls
- Easy to cut to fit on site
- Contours to uneven surfaces

### Cleaning:

Keeping Heronair looking good is easy:

- Lightweight
- Simply roll or lift to clean
- No special cleaning tools needed
- Easy to clean with a high pressure hose

### Colours:




Black

### Ancillaries:


#### > Heronair

PVC edging (H: 10mm, W: 50mm)




Supplied in rolls of 10.1m (33') length with cold welding paste. Comes in black and dark grey. Size: 10mm x 50mm x 10.1m (3/8" x 2" x 33')

PVC snap track (H: 10mm)



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. Supplied with cold welding paste. Comes in dark grey. Size: 10.5mm x 2.5m (13/32" x 8'2")

Connector clips: dual purpose (H: 14mm)



For joining sections of matting together side-to-side or end-to-end. Supplied in packs of 10