

193 Logo Standard[™]

Affordable absorbent printed logo mat



Logo Matting - Logo Mats

193 Logo Standard™

Logo Standard™ can be fully customized with BrilliantStep™ state-of-the-art printing technology allowing 3-dimensional effects, fine lines and colour shading, for each mat to have its truly individual image.

- A durable vinyl backing with smooth finish adapts to any surface
- Tufted cut loop pile consisting of 100% non-crush polyamide 6.0 high twist yarns
- 405 grams of yarns per m²

Recommended use

- Indoor
- For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, speciality stores.
- Medium traffic

Colors:

- Logo

Sizes:

- 120cm x 180cm
- 60cm x 90cm
- 90cm x 120cm
- 90cm x 150cm
- 90cm x 300cm
- 120cm x linm
- 90cm x linm

Accessories:

- 083 Bevelled Nosing 2 mm
- 090 Mat Hold™
- 085 Velcro® Carpet Anchor



WATER RETENTION

CRUSH RESISTANCE

RATING DUST CONTROL

B2 Athy Business Campus
Athy
Co. Kildare
R14 PK74
sales@pittman.ie
01 5312777

1310 Solihull Parkway
Birmingham Business Park
Birmingham
B37 7YB
sales@pittman.uk
0121 630 3527

pittman®

Logo Matting - Logo Mats

Logo Standard™

General

Brand	Notrax
Category	Logo Mats
Product Number	193
Product Family	Industrial & Commercial Matting
Product Group	Logo Matting
Product Name	Logo Standard™
Recommended use	For placement inside entrances of offices, shops, restaurants, grocery shops, bakeries, specialty stores.
Shipping Location	Barendrecht 2992SB, The Netherlands, Chicago, IL 60638, United States
Type	Indoor Absorbant - Printed Logo Mats
Update trigger	20210310-1301
Usage Intensity	Medium traffic

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Reach US	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Sustainability	Recyclable material, Contributes to a cleaner environment by reducing need of cleaning chemicals
Warranty	1

Tests

Comfort Class	LC3
Light Fastness	5
Organic Solvents	4
Rubbing Fastness	4
Salt Water	4
Sanitary Testing	Pass
Shampoo	4
Static Charge	<0.1
Water Fastness	4

Technical Specifications

Absorption Capacity	3 l/m ²
Application	Loose Lay Carpet Mats
Backing	Black vinyl (DOP free)
Edges	Vinyl borders: 2.5 cm on all sides
Material	Frieze 100% polyamide 6.6 high twist yarns
Material Group	Polyamide
Pile Weight (g)	405
Process	Tufting
Yarn Construction	Cut loop pile - frieze