



MERCURY SUB-SURFACE MOUNT STAINLESS STEEL BOLLARD

OVERVIEW

The Mercury Sub Surface Mount Stainless Steel Bollard provides permanent, high-visibility protection for commercial entrances, car parks, service yards, and public spaces.

Manufactured from premium 304-grade stainless steel with a brushed finish, this bollard combines corrosion resistance with a smart, modern appearance. Its Ø114 mm thick-walled tube and bright yellow 3M reflective bands ensure excellent visibility in both daylight and low-light conditions.

Designed for sub surface installation, the bollard is embedded securely into concrete for maximum stability and long-term performance, making it an ideal choice where vehicle control or asset protection is required.

pittman[®]

FEATURES

- Stainless steel tube – durable construction for outdoor protection
- 304-grade stainless steel – excellent corrosion resistance
- Yellow 3M reflective bands – ensures visibility in daylight and low-light conditions
- 240-grit brushed finish – professional appearance for public and commercial settings

TECHNICAL DATA

SPECIFICATIONS	DETAILS
Product Code	SKU: 755847
Height	1300 mm (1000 mm Above ground)
Diameter	2 mm
Thickness	114 mm
Material	304 Stainless Steel
Finish	Brushed 240-grit
Reflective Bands	2 × 375 mm × 24.6 mm 3M yellow reflective bands
Mounting	Sub-Surface

