

563 Sanitop Deluxe™

Slip resistant rubber duckboard



Ergonomic, Anti-fatigue & Safety Matting - Wet Areas Standalone Matting

563 Sanitop Deluxe™

Rubber duckboards provide a comfortable and safe working platform in wet areas with its aggressive slip resistant surface. Large holes and raised studs allow fluids in wet areas or debris in dry areas to fall through leaving the surface clear.

- Ergonomic benefit derived from 20 mm thick worker platform
- Straight edges allow coverage of any area through linking the mats lengthwise or side by side, held together by connectors
- 100% natural rubber compound for general purpose applications
- Cleaning with detergent and water-jet is recommended for extended service life

Recommended use

- Wet/Dry Areas
- For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
- Heavy duty

Colors:

- Black

Sizes:

- 91cm x 152cm

Accessories:

- 563N Sanitop Deluxe™ Ramp
- 563K Sanitop Deluxe™ Connectors



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE



Ergonomic, Anti-fatigue & Safety Matting - Wet Areas Standalone Matting Sanitop Deluxe™

General

Brand	Notrax
Category	Wet Areas Standalone Matting
Product Number	563
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Sanitop Deluxe™
Recommended use	For placement in manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual work stations.
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands
Type	Wet/ Dry Areas - Rubber Working Platforms
Update trigger	20210310-1301
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	True
Sustainability	Recyclable material
Warranty	1

Tests

Surface Flammability	Pass
----------------------	------

Technical Specifications

Application	Industrial Environments
Edges	Attachable bevelled edges are available
Material	Natural rubber
Material Group	Natural rubber
Process	Compression Moulding
Temperature Range	- 40 ° C up to + 120 ° C