

pittman[®]

782 Sky Trax[®]

Top-of-the-line ergonomic experience



Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths 782 Sky Trax[®]

Heavy duty industrial anti-fatigue mat. Tough laminated top surface with ergonomic bubble pattern for extra comfort while standing. RedStop™ slip-resistant backing that prevents the mat from shifting.

- Slip-resistance and freedom of movement; tested R9 according to DIN51130 and BG-rule BGR181
- Featured with RedStop™ slip-resistant backing to prevent mat from shifting
- Available with yellow borders along the sides to comply with OSHA code 1910-144

Recommended use

- Dry Areas
- In manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual workstations. Also suitable for commercial environments including hotels, reception desks, shop counters, department stores, banks, restaurants, etc.
- Heavy duty

Colors:

- Black
- Black/Yellow
- Grey

Sizes:

- 60cm x 91cm
- 91cm x 150cm
- 91cm x 200cm
- 91cm x 300cm
- 91cm x 600cm
- 122cm x linm
- 152cm x linm
- 60cm x linm
- 91cm x linm
- 122cm x 21.9m
- 152cm x 21.9m
- 60cm x 21.9m
- 91cm x 21.9m



WEAR RESISTANCE

SLIP RESISTANCE

ANTI-FATIGUE



pittman[®]

Ergonomic, Anti-fatigue & Safety Matting - Dry Areas Linear Lengths Sky Trax®

General

Brand	Notrax
Category	Dry Areas Linear Lengths
Product Number	782
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Sky Trax®
Recommended use	In manufacturing plants, assembly lines, picking, packing and logistics warehouses, individual workstations. Also suitable for commercial environments including hotels, reception desks, shop counters, department stores, banks, restaurants, etc.
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands, Moselle, MS 39459, United States
Type	Dry Areas - Heavy Duty Industrial
Update trigger	2023-02-17-2
Usage Intensity	Heavy duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Rohs US	Rohs compliant (Restriction of Hazardous Substances).
Warranty	1

Tests

Abrasion Resistance 500	0.1% weight loss
Compression Deflection 1.4	0.52 cm
Compression Deflection 2.8	0.82 cm
Elongation	150%
Fire rating EU	En 13501-1 Cfl-S2
Fire rating US	Pass
Foam Battery	40 lb/in ²
Hardness	95 Shore A
Slip Rating	R9
Coefficient Friction Dry	0.82
Surface Flammability	Pass
Tear Strength	67.5 lbs

