

452 Skywalker[®] PUR ESD

ESD polyurethane mat with bubble pattern



Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

452 Skywalker® PUR ESD

High quality polyurethane foam anti-fatigue mats are reputed for their ultimate comfort in stationary standing positions.

- All four sides have bevelled edges to minimize tripping hazards
- Environmental friendly, produced without use of organic carbon-based blowing agents
- Ergonomically designed bubble surface provides traction and fatigue relief

Recommended use


- Dry Areas
- Ideal for stationary standing workstations, sit-stand desks, packing stations, office environments, reception areas, wait stations, service counters, cashiers
- Medium duty

Colors:

- Black

Sizes:

- 65cm x 140cm
- 65cm x 185cm
- 65cm x 95cm
- 95cm x 125cm
- 95cm x 155cm
- 95cm x 185cm



Ergonomic, Anti-fatigue & Safety Matting - ESD Matting & Accessories

Skywalker® PUR ESD

General

Brand	Notrax
Category	ESD Matting & Accessories
Product Number	452
Product Family	Industrial & Commercial Matting
Product Group	Ergonomic, Anti-fatigue & Safety Matting
Product Name	Skywalker® PUR ESD
Recommended use	Ideal for stationary standing workstations, sit-stand desks, packing stations, office environments, reception areas, wait stations, service counters, cashiers
Shipping Location	Achterzeedijk 57, Unit 15, Barendrecht 2992SB, The Netherlands
Type	Dry Areas - Medium Duty Polyurethane Mats
Update trigger	20210310-1301
Usage Intensity	Medium duty

Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Recycled	False
Sustainability	Recyclable material
Warranty	1

Tests

Abrasion Resistance 1000	150 mg (2.5N)
Elongation	300%
ESD Rg	Rp 10 ⁶ - 10 ⁹ Ω
ESD Rp	Rg 10 ⁶ - 10 ⁹ Ω
Hardness	25 Shore A
Slip Rating	R10
Surface Flammability	Pass
Tear Strength	1.7 N/mm

Technical Specifications

Application	Industrial Environments
Edges	Bevelled edges on all sides
Material	Nitrile rubber blend
Material Group	Polyurethane
Process	Injection Moulding
Temperature Range	- 40 ° C up to + 120 ° C