

# 380 Swisslon XT™

Premium quality barrier matting



# Dust Control Matting - Indoor Contract & Installation Matting

## 380 Swisslon XT™

Premium quality barrier matting designed to remove walked-in moisture and finer dirt particles in large indoor entrance areas, including wall-to-wall applications.

- Great ability to retain moisture (>5.8 litres per m<sup>2</sup>)
- The new tri-colour grit pattern provides outstanding dirt-hiding characteristics

### Recommended use

- Indoor
- For placement in recessed matwell frames (depth 7 mm) or wall-to-wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs
- Heavy traffic

### Colors:

- Charcoal
- Granite
- Grey
- Mocha

### Sizes:

- 120cm x 180cm
- 120cm x 240cm
- 60cm x 90cm
- 90cm x 120cm
- 90cm x 150cm
- 135cm x linm
- 200cm x linm
- 135cm x 20m
- 200cm x 20m

### Accessories:

- 083 Bevelled Nosing 2 mm

WATER RETENTION

CRUSH RESISTANCE

RATING DUST CONTROL

B2 Athy Business Campus  
Athy  
Co. Kildare  
R14 PK74  
sales@pitman.ie  
01 5312777

1310 Solihull Parkway  
Birmingham Business Park  
Birmingham  
B37 7YB  
sales@pittman.uk  
0121 630 3527

# Dust Control Matting - Indoor Contract & Installation Matting

## Swisslon XT™

### General

Brand	Notrax
Category	Indoor Contract & Installation Matting
Product Number	380
Product Family	Industrial & Commercial Matting
Product Group	Dust Control Matting
Product Name	Swisslon XT™
Recommended use	For placement in recessed matwell frames (depth 7 mm) or wall-to-wall installations in larger entrances at hotels, shopping malls, cinemas, public buildings, department stores, banks, restaurants and on stairs
Shipping Location	Barendrecht 2992SB, The Netherlands
Type	Indoor – Contract and Installation Matting
Update trigger	20210310-1301
Usage Intensity	Heavy traffic

### Sustainability

REACH	Reach compliant (Registration, Evaluation, Authorization and Restriction of Chemicals).
Sustainability	Contributes to a cleaner environment by reducing need of cleaning chemicals
Warranty	1

### Tests

Comfort Class	LC2
Fire rating EU	En 13501-1 Cfl-S1
Fire rating US	Pass
Light Fastness	6
Organic Solvents	4
Rubbing Fastness	4
Salt Water	4
Shampoo	4
Static Charge	<0.1
Surface Flammability	Pass
Water Fastness	4

## Technical Specifications

Absorption Capacity	6
Backing	Black vinyl (DOP free)
Dimensional Stability	<0.4
Edges	Vinyl borders: 2.5 cm on both sides
Material	100% polyamide 6.0 yarns
Material Group	Polyamide
Pile Weight (g)	850
Process	Tufting
Tufts	85500
Yarn Construction	Cut loop pile - velours