

## TECHNICAL SPECIFICATIONS

**HINGE FREE:** Wear resistant, warp proof integrated hinge.

**LOCKABLE:** Exclusive tamper-proof safety lock with hidden latch.

**FULL DISPLAY:** 100 % of the display surface visible (lock mounted in the frame not the glazing).

**STRENGTH:** Robust profile and available in 4mm anti-vandal Plexichoc™ or safety glass.

**PRACTICAL:** Doors easily replaceable in case of major vandalism.

**WATERPROOF:** Elastomer seal and anti-condensation vents.

### NOTICE BOARD

Format: single sided – single or dual-door depending on dimensions.

Display area: from 2 to 18 A4.

Profile depth: 30 mm

Glazing: vandal-resistant 4 mm Plexichoc®.

Opening method: side opening (door is reversible) or dual-door.

Locking: tamperproof safety lock with supplied 2 keys.

Waterproofing: elastomer seal.

Back plate finish: galvanised steel back in a white lacquered finish for use with magnets. External back finished in RAL 7032 unless otherwise specified.

Frame finish: silver anodised aluminium or painted in our Vitincom® colour offering.

Installation: wall or post mounting (optional).

Supplied with Procity® magnets (1 per A4).

### Optional post kits:

Post kit: 2 post 60 x 40 mm either silver anodised or painted, delivered with 4 stainless steel mounting brackets.

Installation: concrete directly in the ground or on base plates.\*

Plus post: 60 x 40 mm either silver anodised or painted, delivered with 2 stainless steel mounting brackets.

Used as a central post to align several notice boards.

Installation: concrete directly in the ground.

\*If the product is to be likely to be exposed to strong winds, we strongly recommend post kits to be concreted directly in the ground.

### Optional decorative header panel:

Header panel: 2 mm plasma cut steel.

3 shapes: Dome, Wave or Rectangle

Installation: attached to a wall using pre-drilled mounting holes (fixings not supplied) or on the post kit using fixings provided.

### Other options:

LED kit (supplied for self-assembly)\*

Additional magnets.

\*LED ribbons and transformers are not factory fitted and require installation by a qualified electrician to comply with applicable safety regulations.

## PAINT FINISH



RAL 5010



RAL 9005



RAL 3004



RAL 6005



RAL 8017



Anodised

