

Cycle Compounds Specification Sheet



Sizes Available:

<u>Height</u>	<u>Width</u>	<u>Depth</u>	<u>Cycle Compound Features</u>	<u>Bike Capacity</u>
2325mm	5500mm	3000mm	Lockable Gate	16 Bikes
2325mm	5500mm	6000mm	Lockable Gate	32 Bikes
2325mm	5500mm	9000mm	Lockable Gate	48 Bikes
2625mm	5500mm	3000mm	Lockable Gate & Security Canopy	16 Bikes
2625mm	5500mm	6000mm	Lockable Gate & Security Canopy	32 Bikes
2625mm	5500mm	9000mm	Lockable Gate & Security Canopy	48 Bikes

Cycle Compound Construction:

- Hasp padlock locking
- Side panels manufactured from clear Perspex
- Must be bolted to 250mm thick concrete
- Delivered in components for onsite easy – assembly
- Installation available from the QMP team – please speak to sales for a quotation
- All metal parts powder coated for improved weather resistance
- Optional central security canopy

Paint Finish:

- Three stage pre-treatment and phosphate coating
- Carcass and doors powder coated with one coat Epoxy Polyester Full gloss powder, stoved at 180 deg. C. including Germ Guard antibacterial compound
- Cycle Compound available with various powder coated colour options

Cycle Compound Colours:

Red	RAL 3003
Green	RAL 6028
Blue	RAL 5017
Black	RAL 7024
Light Grey	RAL 7035

Equipment Cleaning & Maintenance instructions:

- Clean paint work periodically with warm soapy water

